

GJS-6010

Features


- Advanced internal structure design
- Easy to re-enter, it never requires re-entry tool it
- The closure is spacious enough for winding and storing fibers
- Fiber Optic Splice Trays(FOSTs) are design in SLIDE-IN-LOCK and its opening angle is about 90°
- The curved diameter meets with international standard
- Easy and fast to increase and reduce FOSTs
- Straight-through for uncutting and branching for cutting the fiber


Applications


- ◆ Suitable for bunchy & ribbon fibers
- ◆ Aerial, underground, wall-mounting, hand hole-mounting

 Pole-mounting and duct-mounting

Structural Drawing







Ordering Information

Optical Splice Trays



#002 160X122X10mm

#020 160X108X11mm

#004 180X127X14mm

Туре	Fibers/Tray	Max. Capacity	Tray#	Suitable Cable Dia. allowed(mm)	
GJS-6010 I(Bunchy)	12-24F	216	002	2 round ports:16mm	
GJS-6010II(Bunchy)	12-24F	192	020	2 round ports:20mm	
GJS-6010 III(Ribbon)	72F	432	004	2 round ports:23mm	

Accessories

Standard Accessories:

No.	Name	Quantity	
1	Seal tape	1 roll	
2	Insulation tape	1 roll	
3	Abrasive cloth	1 pc	
4	Earthing wire	1pc	
5	Nylon tie	1 set	W.
6	Labeling paper	1 pc	1 2 3 4 5 6 7 8 8 8 8 8 13 1 1 2 3 4 5 6 7 8 7 8 8 8 8 13 1 1 2 3 4 5 6 7 8 7 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8

No.	Name	Quantity	
7	Desiccant	2 bags	GEL MAN AND THE PROPERTY OF TH
8	measuring paper	1 pc	without the substitute of the
9	Special wrench	1 pc	4
10	Hexagon wrench	2 pcs	<u> </u>
11	Hanging hook	1 set	for for
12	Heat shrinkable protective sleeve	1 bag	

Optional Accessories:

No.	Name	Quantity	
1	Pressure testing valve	1 pc	e
2	Earthing deriving device	1 pc	
3	Buffer tube for bunchy fiber	1 roll	

No.	Name	Quantity	
4	Pole mounting bracket	1 set	
5	Wall mounting bracket	1 set	<u> </u>
6	Buffer tube for ribbon fiber	1 roll	