

Fiber Optics Distribution Box


Overview

This mini style distribution box is widely applied in the FTTX network to connect drop cable and ONU devices through fiber port. It supports splicing, distribution, mechanical connection and wall mounted installation. The capacity of this box can be 1 core, 2 cores and 4 cores.



Features

- ABS material used ensures the body strong and light
- Easy installations: Mount on wall
- Easy operation: plug fiber with no need to open the shell
- Fiber cable inlets from every direction, supporting the cable inlets for different scenarios.
- Adoptable adapter: SC, LC



Dimensions and Capability	
Adapter Capacity	Accommodates 4 fibers with LC adapters; 2 fibers with SC adapters
Number of Cable Entrance/Exit	Up to 4
Pigtail	G652D Φ0.9mm, 0.5m or as per request
Drop Cable(flat)	Indoor flat drop cable 2 x 3mm
Drop Cable(round)	Φ5mm~ Φ10mm
Curvature Radius	≥15mm
Optional Accessories	Adapters, Pigtails, Heat Shrink Tubes

Operation Conditions	
Temperature	-5℃ -- 60℃
Humidity	90% at 30℃
Air Pressure	70kPa – 106kPa

Shipping Information	
Package Contents	Mini terminal box, 1 unit; Wall mount installation accessories, 1 set
Material	Carton box
Weight	0.65kg
Lead Time	10-15 working days normally