

# CABINETS

## 10 INCH CABINET

### Standard

- Comly with ANSI/EIA RS-310-D、IEC60297-2、DIN41494;PARAT1;DIN41494;PART7.

### Material

- SPCC Cold Rolled Steel;
- Thickness:Mounting Profile:1.2mm; others:1.0mm.

### Colour

- SE:RAL7035
- SE:RAL9004

### Loading Capacity

- Static loading:60KG



# CABINETS

## 10 INCH CABINET

### Feature

- Flat packing and patent frame, packing time is less than 5 minutes, around 1/3~1/4 assembled original volume when flat pack.
- Cable entry on both of top cover and bottom panel.
- Steel front door, opening direction of door can be changed, turning angle of front door is over 180 degrees.
- Different optional style of doors
- Wall mounted panel, convenience for installation, locked from inside with screw, avoiding to be stolen or accidentally dropped.
- Flat side panel, easy installation.
- Installation depth of mounting profile can be available changed.
- 19" standard installation.



### Main Part

S/N	Specification	Qty	Material	Surface Finish	Remark
1	Back frame	1	SPCC t1.0	Powder coated	----
2	Side frame	2	SPCC t1.0	Powder coated	----
3	Top cover	1	SPCC t1.0	Powder coated	----
4	Bottom	1	SPCC t1.0	Powder coated	----
5	Front frame	1	SPCC t1.0	Powder coated	See next page
6	Front door	1	5MM toughed glass door/ SPCC t1.2	Powder coated	Available on request, See page 86
7	Side panel	2	SPCC t1.0	Powder coated	----
8	19" rails	2	SPCC t1.2	Powder coated	----
A	M6 screw& nuts	10	Steel	Color zinc	20pcs for over 12U
B	Trox tooling	1	Steel	Black	----

### Specification

Model No.	RU	Width (mm)	Depth(D)(mm)	Height(H)(mm)	Packing dimension (mm)
SV.6406.01.■00	6	350	300	370	370*320*390
SV.6409.01.■00	9	350	300	500	370*320*520
SV.6412.01.■00	12	350	300	635	370*320*650
SV.6415.01.■00	15	350	300	770	370*320*790